

#### Neutrino Flux At Detector

- Neutrino beam is much wider than detector
  - ◆ Angular spread in decays: can't control
  - ◆ Angular divergence of muon beam
- Larger muon beam divergence, smaller flux
  - Narrow muon beam maximizes flux
  - ◆ Uncertainty in muon divergence → uncertainty in flux
  - ◆ If decay divergence dominates muon divergence
    - ★ Narrowing muon divergence provides little benefit
    - **★** Lower uncertainty in flux
- Larger event rates
  - Small statistical uncertainty ( $\sim 0.001$  relative)
  - ◆ Requires low flux uncertainty



## Computing Flux

• Flux is convolution of muon angular distribution with decay angular distribution

$$\rho(\theta_x, \theta_y) = \int \rho_{\text{Muon}}(\theta_x - \theta'_x, \theta_y - \theta'_y) \rho_{\text{Decay}}(\theta'_x, \theta'_y) d\theta'_x d\theta'_y$$

- $N d\Omega_{\rm Detector} \rho(0,0)$  is flux on detector
- If both Gaussian, muon beam  $\sigma_x$ ,  $\sigma_y$ , decays  $\sigma_0$


$$\frac{\phi(\sigma_x, \sigma_y, \sigma_0)}{\phi(0, 0, \sigma_0)} = \frac{1}{\sqrt{1 + \frac{\sigma_x^2}{\sigma_0^2} \sqrt{1 + \frac{\sigma_y^2}{\sigma_0^2}}}}$$

• Uncertainty in flux comes from taking derivates of this with respect to  $\sigma_x$ ,  $\sigma_y$ 



### Fitting Model Parameters

• Monte-Carlo calculation of event rates at detector as a function of muon beam divergence (Crisan & Geer)



- Fit:  $\sigma_0 = 0.42/\gamma$ 
  - ◆ Energy-weighted cross section
- Uncertainty: slope
  - ◆ Near zero divergence: small slope
  - ◆ Slope decreases to zero linearly
  - ◆ Larger divergence: larger slope, despite smaller flux!



# **Production Straight**

- Divergence is  $\sqrt{\gamma \epsilon}$ 
  - $\gamma = (1 + \alpha^2)/\beta$
- Large divergence at ends
  - Smaller  $\beta$
  - Large  $\alpha$ 
    - \* Required to make  $\beta$  rise quickly
- Long drift in middle of straight
  - Keeps  $\alpha$  down, reducing  $\gamma$
- Larger divergence leads to
  - ◆ Lower flux
  - ◆ Higher uncertainty



### **Analysis**

- Too must uncertainty coming from ends
  - ◆ Very little flux comes from there
  - ◆ Insert bends so they aren't pointed toward detector
    - ★ Very little loss: 8%
    - ★ Required bend:  $\approx 29$  mrad.
    - ★ Only 25% of muons decaying toward detector, not 35%
- Uncertainty from middle still too high: 1% (want 0.1%???)
  - Assumed uncertainty in  $\sigma_{\theta}$  of 15%
    - ★ Make better measurement of muon beam
    - **★** Detectors placed in beam
    - $\star$  Electron backgrounds
  - ◆ Measure neutrino beam (Norem)
    - ★ Hodoscopes in a tunnel a couple hundred meters downstream
    - **★** Need several to get angular distribution
    - ★ Too close to source for one hodoscope to give angular distribution
  - ◆ Need high accuracy current measurement also

